



tyres up ↑

costs down ↓

The **Tyre Elevator** made by

**KEIPER**

- for passenger-car and truck tyres
- lengths varying from 3 to 25 m
- in stationary or mobile design
- areas of application: tyre wholesale, tyre services, repair shops, vulcanizing companies, worn-out tyre recycling

## Technical specifications:

Set-up:	rugged steel frame
Lengths:	3 – 25 m
Required space:	below 1 m <sup>2</sup>
Power supply:	three-phase current 230 / 400 V (standard)
Conveying capacity:	approximately 10 – 15 tyres / min.
Conveying velocity:	v = approximately 0.30 m / sec. (standard)
Conveying chain:	rugged and low-wear steel roller chain, with carrier forks, which are 1,500 – 2,000 mm apart
Tyre size:	passenger-car and truck tyres (without wheel rims) up to an outer diameter of 1,000 mm and an inner diameter of 500 mm
Tyre loading:	manually, from floor level
Design:	standard version and special designs



*Mobile tyre elevator in a tyre warehouse feeding various warehouse levels.*



*Special design of the tyre elevator for heavy truck tyres.*



*Mobile tyre elevators, manually movable, for conveying heights between 4 and 8 m, in a large tyre-depot.*



Additional information can be obtained at:

**LUDWIG KEIPER GmbH & Co. KG**

Landsbergstrasse 12 – 15  
Germany · 67823 Obermoschel  
Phone: +49 (0) 63 62 / 7 21  
Fax: +49 (0) 63 62 / 34 30

info@keiperkg.de · www.tyrelift.de